

AMENDMENTS TO THE CLAIMS:

Please amend the claims as follows:

1. (Currently amended) A printed wiring board comprising:

an insulating board which includes a plurality of electrically insulating layers which are laminated;

an electronic component which is built in the insulating board;

a signal transmitting lead transmitting a high-frequency signal which is provided at an interlayer between the electrically insulating layers;

an auxiliary lead which is provided on the insulating board while the auxiliary lead is not in electrical contact with the signal transmitting lead;

the auxiliary lead is not in electrical contact with a ground lead; and

an electromagnetic shielding layer made of a magnetic material having magnetic loss which covers at least a part of the auxiliary lead, wherein a signal is not carried to the auxiliary lead.
- 2-3. (Cancelled)
4. (Previously presented) The printed wiring board as claimed in claim 1, wherein an insulating film is provided between the auxiliary lead and the electromagnetic shielding layer.
5. (Previously presented) The printed wiring board as claimed in claim 1, wherein the signal transmitting lead has lead regions which are opposite to each other, and the auxiliary lead is provided between the opposite lead regions.
6. (Withdrawn) A printed wiring board as claimed in claim 1, wherein the auxiliary lead is provided between the signal transmitting lead and the electronic component.

7. (Withdrawn) A printed wiring board as claimed in claim 1, wherein the auxiliary lead is provided opposite to a component surface in which strength of unnecessary radiation from the electronic component is higher in both component surfaces of the electronic component.

8. (Withdrawn) A printed wiring board as claimed in claim 1, wherein the auxiliary lead is provided opposite to a terminal forming surface of the electronic component.

9. (Withdrawn) A printed wiring board as claimed in claim 1, wherein the auxiliary lead is provided opposite to the component surface located on a reverse side of the terminal forming surface of the electronic component.

10. (Withdrawn) A printed wiring board as claimed in claim 1, wherein the auxiliary lead is provided opposite to the terminal forming surface of the electronic component and the component surface located on the reverse side of the terminal forming surface of the electronic component respectively.

11. (Withdrawn) A printed wiring board as claimed in claim 1, wherein the plurality of electronic components are provided, and the auxiliary lead is provided between the plurality of electronic components.

12. (Withdrawn) A printed wiring board as claimed in claim 1, wherein the auxiliary lead is provided on a periphery of the electronic component so as to surround the electronic component.

13. (Withdrawn) A printed wiring board as claimed in claim 1, wherein the auxiliary lead comprises a first auxiliary lead which covers one of the surfaces of the electronic component and a second auxiliary lead which is provided on the periphery of the electronic component so as to surround the electronic component, and a conductor which electrically

connects the first auxiliary lead to the second auxiliary lead is provided in the electrically insulating layer.

14. (Withdrawn) A printed wiring board as claimed in claim 13, wherein the plurality of conductors are provided so as to surround a side face of the electronic component, and the conductors are arranged so, that opposite directions of the conductors which are adjacent to each other are unparallel to a width direction of the side face of the electronic component and the opposite directions are intersected in sequence.

15. (Withdrawn) A printed wiring board as claimed in claim 1, wherein the electromagnetic shielding layer is provided on both surfaces of the auxiliary lead.

16. (Withdrawn) A printed wiring board as claimed in claim 1, wherein an electromagnetic shielding layer which covers at least a part of the signal transmitting lead is further provided.

17. (Withdrawn) A printed wiring board as claimed in claim 16, wherein both surfaces of the signal transmitting lead are covered with the electromagnetic shielding layer.

18. (Withdrawn) A printed wiring board as claimed in claim 16, wherein the insulating film is provided between the signal transmitting lead and the electromagnetic shielding layer which covers the signal transmitting lead.

19. (Withdrawn) A printed wiring board as claimed in claim 18, wherein the signal transmitting lead is provided on both surfaces of the electrically insulating layer respectively, the conductor which connects the signal transmitting leads on both surfaces are provided so that the conductor penetrates through the electrically insulating layer, and the insulating film and the electromagnetic shielding layer are arranged apart from the conductor.

20. (Withdrawn) A printed wiring board as claimed in claim 1, wherein the electrically insulating layer is made of a composite material which is formed by mixing an epoxy resin and an inorganic filler.

21. (Withdrawn) A printed wiring board as claimed in claim 1, wherein the auxiliary lead is connected to the ground potential and a length of the electromagnetic shielding layer is set to one fourth of a subject wavelength of suppression.

22. (Withdrawn) A printed wiring board as claimed in claim 1, wherein the length of the electromagnetic shielding layer is set to half the subject wavelength of the suppression.

23. (Withdrawn) A manufacturing method of a printed wiring board which includes an insulating board which includes a plurality of electrically insulating layers which are laminated, an electronic component which is built in the insulating board, a signal transmitting lead which is provided at an interlayer between the electrically insulating layers, an auxiliary lead which is provided on the insulating board in a state that the auxiliary lead is not in electrical contact with the signal transmitting lead, and an electromagnetic shielding layer which covers at least a part of the auxiliary lead, comprising the steps of: preparing a transfer forming material and pattern-forming the auxiliary lead on the transfer forming material; pattern-forming the electromagnetic shielding layer on the auxiliary lead layer on the transfer forming material; and transferring the auxiliary lead from the transfer forming material to the electrically insulating layer by making the electromagnetic shielding layer about on the electrically insulating layer.

24. (Withdrawn) A manufacturing method of a printed wiring board as claimed in claim 23, further comprising the step of pattern-forming the electromagnetic shielding layer on the auxiliary lead layer which is transferred to the electrically insulating layer.